

FRONT TRACTOR TYRES

KNK50

Product Code	Tyre Size / Ply Rating	TT/TL	Inflated Unloaded Dimensions		Load Index	Speed Index	Load & Pressure			
			Section Width	Overall Diameter			Tyre Load Capacity	Tyre Pressure At Max. Load	Dynamic Rolling Circumference	Static Loaded Radius
			(mm)	(mm)			(Kg)	(Psi)	(mm)	(mm)
3003	7.50-15 8PR	TT	205	780	99	A6	775	52	2325	350
3122	6.00-16 6PR	TT	165	735	88	A6	560	48	2206	335
3123	6.00-16 8PR	TT	165	735	93	A6	650	48	2206	335
3222	6.50-16 6PR	TT	175	760	91	A6	615	45	2277	345
3223	6.50-16 8PR	TT	175	760	97	A6	730	54	2277	345
3423	7.50-16 8PR	TT	205	805	103	A6	875	54	2404	363
3523	7.50-18 8PR	TT	205	860	106	A6	950	54	2575	390
3623	7.50-20 8PR	TT	205	915	108	A6	1000	49	2747	417
3652	9.5-20 6PR	TT	241	940	101	A6	825	30	2818	427
3653	9.5-20 8PR	TT	241	940	106	A6	950	35	2817	427
3663	9.5-20 8PR	TL	241	940	106	A6	950	35	2817	427
3673	11.2-20 8PR	TT	285	1005	113	A6	1150	38	3001	453
3683	11.2-20 8PR	TL	285	1005	113	A6	1150	38	3001	453

KNK50